Package: rcrisp (via r-universe)

October 28, 2026

Title Automate the Delineation of Urban River Spaces

Version 1.0.0

Description Provides tools to automate the morphological delineation of riverside urban areas based on a method introduced in Forgaci (2018) <doi:10.7480/abe.2018.31>. Delineation entails the identification of corridor boundaries, segmentation of the corridor, and delineation of the river space using two-dimensional spatial information from street network data and digital elevation data in a projected CRS. The resulting delineation can be used to characterise spatial phenomena that can be related to the river as a central element.

License Apache License (>= 2)

URL https://cityriverspaces.github.io/rcrisp/, https://github.com/CityRiverSpaces/rcrisp, https://doi.org/10.5281/zenodo.15793526

BugReports https://github.com/CityRiverSpaces/rcrisp/issues

Depends R (>= 4.1.0)

Imports checkmate, cli, dbscan, dplyr, lwgeom, osmdata, rcoins, rlang, rstac, sf (>= 0.9.0), sfheaders, sfnetworks, stringr, terra, tidygraph, units, visor

Suggests autotest, ggplot2, knitr, purrr, rmarkdown, testthat (>= 3.0.0), withr

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE, roclets = c(``namespace'', ``rd'', ``srr::srr_stats_roclet''))

Config/roxygen2/version 8.1.1

Config/pak/sysreqs libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev libglpk-dev libicu-dev libjpeg-dev libpng-dev libxml2-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev

Repository https://rbanism.r-universe.dev

Date/Publication 2026-10-20 18:48:41 UTC

RemoteUrl https://github.com/CityRiverSpaces/rcrisp

RemoteRef HEAD

RemoteSha 03fa30690503bd832f6afab63c60b5f2ee57a316

Contents

as_bbox . . . 3
as_crs . . . 3
as_network . . . 4
bucharest_dambovita . . . 5
cache_directory . . . 6
check_cache . . . 6
clean_network . . . 7
clear_cache . . . 7
default_stac_dem . . . 8
define_aoi . . . 8
delineate . . . 10
delineate_city_river . . . 11
delineate_corridor . . . 12
delineate_riverspace . . . 14
delineate_segments . . . 15
delineate_valley . . . 15
delineation . . . 16
flatten_network . . . 17
geom_delineation . . . 17
get_dem . . . 19
get_dem_example_data . . . 20
get_osm . . . 21
get_osm_bb . . . 22
get_osm_buildings . . . 23
get_osm_city_boundary . . . 23
get_osm_example_data . . . 24
get_osm_railways . . . 25
get_osm_river_centerline . . . 25
get_osm_river_surface . . . 26
get_osm_streets . . . 27
get_river_aoi . . . 28
get_stac_asset_urls . . . 29
get_utm_zone . . . 29
load_dem . . . 30
osmdata_as_sf . . . 31
plot.delineation . . . 31
print.delineation . . . 32
print.summary.delineation . . . 33

reproject 33
summary.delineation 34

Index **36**

`as_bbox` *Get the bounding box from the x object*

Description

If the x does not have a CRS, WGS84 is assumed.

Usage

```
as_bbox(x)
```

Arguments

`x`	Simple feature object (or compatible) or a bounding box, provided either as a matrix (with x, y as rows and min, max as columns) or as a vector (xmin, ymin, xmax, ymax)

Value

A bbox object as returned by `sf::st_bbox()`

Examples

```
library(sf)
bounding_coords <- c(25.9, 44.3, 26.2, 44.5)
bb <- as_bbox(bounding_coords)
class(bb)
st_crs(bb)
```

`as_crs` *Standardise the coordinate reference system (CRS) of an object*

Description

Standardise the coordinate reference system (CRS) of an object

Usage

```
as_crs(x, allow_geographic = FALSE)
```

Arguments

x	An object of class sf, sfc, bbox, or a numeric or character vector representing a CRS (e.g., EPSG code). If numeric, the value should be an unrestricted positive number representing a valid EPSG code.
allow_geographic	Logical, whether to allow geographic CRS (lat/lon).

Value

An object of class sf::crs with a valid CRS.

Examples

```
library(sf)

# Standardise a numeric EPSG code
as_crs(4326, allow_geographic = TRUE)

# Standardise a character EPSG code
as_crs("EPSG:4326", allow_geographic = TRUE)

# Standardise a bbox object
bb <- st_bbox(c(xmin = 25.9, ymin = 44.3, xmax = 26.2, ymax = 44.5),
              crs = 4326)
as_crs(bb, allow_geographic = TRUE)

# Standardise a simple feature object
bb_sfc <- st_as_sfc(bb)
bb_sf <- st_as_sf(bb_sfc)
as_crs(bb_sf, allow_geographic = TRUE)
as_crs(bb_sfc, allow_geographic = TRUE)
```

---

as_network *Create a network from a collection of line strings*

Description

Create a network from a collection of line strings

Usage

```
as_network(edges, flatten = TRUE, clean = TRUE, na_action = "warn")
```

Arguments

edges	An sf::sf or sf::sfc_LINESTRING object with the network edges
flatten	Whether all intersections between edges should be converted to nodes

clean — Whether general cleaning tasks should be run on the generated network (see `clean_network()` for the description of tasks)

na_action — A case-insensitive character string specifying how to deal with missing values in non-geometry columns of `edges`. Possible values:

- `"warn"` (default): issue a warning if any `NA` values are found.
- `"error"`: stop with an error if any `NA` values are found.
- `"ignore"`: silently proceed without checking for `NA` values
- `"impute"`: replace `NA` values before building the network. For character columns, `NA`s are replaced with `"unknown"`; for numeric columns, `NA`s are replaced with the column median.

Value

An `sfnetworks::sfnetwork` object

Examples

```
edges <- sf::st_sfc(
  sf::st_linestring(matrix(c(0, 0, 1, 1), ncol = 2, byrow = TRUE)),
  sf::st_linestring(matrix(c(0, 1, 1, 0), ncol = 2, byrow = TRUE)),
  crs = sf::st_crs("EPSG:32635")
)

# Run with default values
as_network(edges)

# Only build the spatial network
as_network(edges, flatten = FALSE, clean = FALSE)
```

---

bucharest_dambovita *rcrisp example delineation data for Bucharest*

Description

Delineation generated with rcrisp example data found at https://zenodo.org/records/16325879

Usage

```
bucharest_dambovita
```

Format

A list of sf objects representing:

valley The valley boundaries of river Dâmbovița.

corridor The corridor boundaries of river Dâmbovița.

segments Corridor segments of river Dâmbovița.

riverspace River space of Dâmbovița.

cache_directory *Return the cache directory used by the package*

Description

By default, the user-specific directory as returned by `tools::R_user_dir()` is used. A different directory can be used by setting the environment variable `CRISP_CACHE_DIRECTORY`. This can also be done by adding the following line to the `.Renviron` file: `CRISP_CACHE_DIRECTORY=/path/to/crisp/cache/dir`.

Usage

```
cache_directory()
```

Value

The cache directory used by rcrisp.

Examples

```
cache_directory()
```

check_cache *Check cache*

Description

A message is displayed if the cache size is > 100 MB or if it includes files older than 30 days.

Usage

```
check_cache()
```

Value

`NULL`

Examples

```
check_cache()
```

clean_network *Clean a spatial network*

Description

Subdivide edges by adding missing nodes, (optionally) simplify the network (see `simplify_network()`), remove pseudo-nodes, and discard all but the main connected component.

Usage

```
clean_network(network, simplify = TRUE)
```

Arguments

`network`	A network object of class `sfnetworks::sfnetwork`
`simplify`	Whether the network should be simplified with `simplify_network()`

Value

A cleaned network object of class `sfnetworks::sfnetwork`

Examples

```
bucharest_osm <- get_osm_example_data()
edges <- dplyr::bind_rows(bucharest_osm$streets,
                          bucharest_osm$railways)
network <- sfnetworks::as_sfnetwork(edges, directed = FALSE)
clean_network(network)
```

clear_cache *Remove cache files*

Description

Remove files from cache directory either before a given date or entirely.

Usage

```
clear_cache(before_date = NULL)
```

Arguments

`before_date`	Date before which cache files should be removed provided as object of class `Date` or as a case dependent character vector accepted by `as.Date()`

Value

NULL

Examples

```
# Clear all cache
clear_cache()

# Clear cache before given date
before_date <- as.Date("1-1-1999", "%m-%d-%Y")
clear_cache(before_date = before_date)
```

---

default_stac_dem *Default STAC collection*

Description

Endpoint and collection ID of the default STAC collection where to access digital elevation model (DEM) data. This is the global Copernicus DEM 30 dataset hosted on AWS, as listed in the Earth-Search STAC API endpoint. Note that AWS credentials need to be set up in order to access the data (not the catalog). References:

- EarthSearch STAC API
- Copernicus DEM
- AWS Copernicus DEM datasets
- Data license

Usage

```
default_stac_dem
```

---

define_aoi *Define delineation parameters within an area of interest*

Description

Define delineation parameters within an area of interest

Usage

```
define_aoi(
  city_name,
  river_name,
  crs = NULL,
  network_buffer = 3000,
  dem_buffer = 2500,
  buildings_buffer = 100
)
```

Arguments

city_name	A character vector of length one
river_name	A character vector of length one
crs	The projected Coordinate Reference System (CRS) to use. If not provided, the suitable Universal Transverse Mercator (UTM) CRS is selected
network_buffer	Add a buffer (an integer in meters) around river to retrieve additional data (streets, railways, etc.). Default is 3000 m.
dem_buffer	Size of the buffer region (in meters) around the spatial network to retrieve the DEM.
buildings_buffer	Add a buffer (an integer in meters) around the river to retrieve additional data (buildings). Default is 100 m.

Value

A list with delineation parameter values, namely `city_name` and `river_name` as character vectors of length one, bb as object of class `sf::bbox`, `crs` as object of class `sf::crs`, and `network_buffer`, `dem_buffer` and `buildings_buffer` as numerical vector of length one.

Examples

```
# Get default parameters in AOI
aoi <- define_aoi("Bucharest", "Dâmbovița")

# Get parameters in AOI with custom CRS
aoi <- define_aoi("Bucharest", "Dâmbovița",
                  crs = "EPSG:3844")  # National projected CRS


# Get parameters in AOI with non-default buffers
aoi <- define_aoi("Bucharest", "Dâmbovița",
                  network_buffer = 2000,
                  dem_buffer = 2000,
                  buildings_buffer = 150)
```

`delineate` *Delineate a corridor around a river*

Description

Given a set of delineation parameters and input data, carry out corridor delineation, corridor segmentation and/or riverspace delineation as indicated by the user.

Usage

```
delineate(
  aoi,
  osm,
  dem = NULL,
  corridor_init = "valley",
  max_iterations = 10,
  capping_method = "shortest-path",
  angle_threshold = 100,
  corridor = TRUE,
  segments = FALSE,
  riverspace = FALSE
)
```

Arguments

`aoi`	A list of delineation parameters for an area of interest, namely `$city_name`, `$river_name`, `$crs`, `$network_buffer`, `$dem_buffer`, and `$buildings_buffer`. For more info see `define_aoi()`.
`osm`	A list with OpenStreetMap data sets within the `aoi`, as objects of class `sf::sfc`
`dem`	Digital elevation model (DEM) of the region (only used if `corridor_init` is `"valley"`)
`corridor_init`	How to estimate the initial guess of the river corridor. It can take the following values: • "valley": use the river valley boundary, as estimated from a Digital Elevation Model (DEM) (for more info see `delineate_valley()`) • numeric or integer: use a buffer region of the given size (in meters) around the river centerline • An `sf::sf` or `sf::sfc` object: use the given input geometry
`max_iterations`	Maximum number of iterations employed to refine the corridor edges (see `corridor_edge()`).
`capping_method`	The method employed to connect the corridor edge end points (i.e., to "cap" the corridor), as character vector of length one. See `cap_corridor()` for the available methods.
`angle_threshold`	Only network edges forming angles above this threshold (in degrees) are considered when forming segment edges. See `delineate_segments()` and `rcoins::stroke()`. Only used if `segments` is TRUE.

corridor	Whether to carry out the corridor delineation
segments	Whether to carry out the corridor segmentation
riverspace	Whether to carry out the riverspace delineation

Details

The returned delineation class is a list wrapping objects of class sf::sfc_POLYGON or sf::sfc_MULTIPOLYGON which can be retrieved through subsetting and converted to other common spatial classes in typical sf- or terra-based workflows.

Corridor delineation depends on the availability of OpenStreetMap street and railway data around the river. Sparse OSM data, especially too few river crossings, may lead to failed delineation.

Value

A list object of class delineation containing zero or more of the following elements: "valley", "corridor", "segments", and "riverspace", each as an sf::sfc_POLYGON or sf::sfc_MULTIPOLYGON object (depending on the geometry of the input data). The list contains only the geometries corresponding to the delineation steps that were carried out (e.g., if segments is FALSE, the list will not contain a "segments" element). In any case, the returned object also contains the base layers and a list aoi with the parameters used for delineation.

Examples

```
# Define delineation parameters within area of interest
aoi <- define_aoi("Bucharest", "Dâmbovița")

# Get data
osm <- get_osm(aoi)
dem <- get_dem(aoi, osm)

# Delineate with defaults
delineate(aoi, osm, dem)

# Carry out all delineations
delineate(aoi, osm, dem, segments = TRUE, riverspace = TRUE)
```

---

delineate_city_river *Delineate a corridor around a river*

Description

This is a convenience function used for quick delineation. With only the city name and river name as input, it uses default delineation parameters, it retrieves OSM and DEM data and returns a list with all three delineations.

Usage

```
delineate_city_river(
  city_name,
  river_name,
  corridor = TRUE,
  segments = TRUE,
  riverspace = TRUE
)
```

Arguments

city_name	A character vector of length one.
river_name	A character vector of length one.
corridor	Whether to carry out the corridor delineation. Default is TRUE.
segments	Whether to carry out the corridor segmentation. Default is TRUE.
riverspace	Whether to carry out the riverspace delineation. Default is TRUE.

Value

A list with the valley, corridor, segments, and riverspace geometries as `sf::sfc_POLYGON` objects.

Examples

```
delineate_city_river("Bucharest", "Dâmbovița")
```

---

delineate_corridor *Delineate a river corridor on a spatial network*

Description

The corridor edges on the two river banks are drawn on the provided spatial network starting from an initial guess of the corridor (based e.g. on the river valley).

Usage

```
delineate_corridor(
  network,
  river,
  corridor_init = 1000,
  max_width = 3000,
  max_iterations = 10,
  capping_method = "shortest-path"
)
```

Arguments

network	The spatial network of class sfnetworks::sfnetwork to be used for the delineation. Required, no default.
river	A (MULTI)LINESTRING simple feature geometry of class sf::sf or sf::sfc representing the river centerline. Required, no default.
corridor_init	How to estimate the initial guess of the river corridor. It can take the following values: • numeric or integer: use a buffer region of the given size (in meters, positive, unrestricted) around the river centerline • An sf::sf or sf::sfc object: use the given input geometry
max_width	A positive number representing the (approximate) maximum width of the corridor in meters. The upper limit is unrestricted. The spatial network is trimmed by a buffer region of this size around the river.
max_iterations	A positive integer greater than 0, with upper limit unrestricted, representing the maximum number of iterations employed to refine the corridor edges (see corridor_edge()).
capping_method	Case-insensitive character vector of length 1 with the method employed to connect the corridor edge end points (i.e. to "cap" the corridor). See cap_corridor() for the available methods.

Value

A simple feature geometry of class sf::sfc_POLYGON representing the river corridor

Examples

```
bucharest_osm <- get_osm_example_data()
streets <- bucharest_osm$streets
railways <- bucharest_osm$railways
river <- bucharest_osm$river_centerline

# Delineate with default values
network <- rbind(streets, railways) |> as_network()
delineate_corridor(network = network, river = river)

# Delineate with user-specified parameters
bucharest_dem <- get_dem_example_data()
corridor_init <- delineate_valley(dem = bucharest_dem, river = river)
delineate_corridor(network = network, river = river,
                   corridor_init = corridor_init,
                   max_width = 4000, max_iterations = 5,
                   capping_method = "direct")
```

`delineate_riverspace` *Delineate the space surrounding a river*

Description

Delineate the space surrounding a river

Usage

```
delineate_riverspace(
  river,
  occluders = NULL,
  density = 1/50,
  ray_num = 40,
  ray_length = 100
)
```

Arguments

`river`	List with river surface and centerline
`occluders`	Geometry of occluders
`density`	Density of viewpoints
`ray_num`	Number of rays as numeric vector of length one
`ray_length`	Length of rays in meters as numeric vector of length one

Details

For riverspace delineation, OSM water polygons intersecting the river centerline are treated as part of the river, including connected water bodies such as lakes and reservoirs. Viewpoints are calculated from water edges where available, and from the river centerline when river surface polygons are missing or partial.

Value

Riverspace as object of class `sf::sfc_POLYGON`

Examples

```
bucharest_osm <- get_osm_example_data()
delineate_riverspace(bucharest_osm$river_surface, bucharest_osm$buildings)
```

delineate_segments *Split a river corridor into segments*

Description

Segments are defined as corridor subregions separated by river-crossing transversal lines that form continuous strokes in the network.

Usage

```
delineate_segments(corridor, network, river, angle_threshold = 100)
```

Arguments

corridor	The river corridor as a simple feature geometry of class sfc_POLYGON
network	The spatial network of class sfnetwork to be used for the segmentation
river	The river centerline as a simple feature geometry of class sf::sf or sf::sfc
angle_threshold	Only consider angles above this threshold (in degrees) to form continuous strokes in the network. The value can range between 0 and 180, with the default set to 100. See rcoins::stroke() for more details.

Value

Segment polygons as a simple feature geometry of class sf::sfc_POLYGON

Examples

```
bucharest_osm <- get_osm_example_data()
corridor <- bucharest_dambovita$corridor
network <- rbind(bucharest_osm$streets, bucharest_osm$railways) |>
  as_network()
river <- bucharest_osm$river_centerline
delineate_segments(corridor, network, river)
```

delineate_valley *Extract the river valley from the DEM*

Description

The slope of the digital elevation model (DEM) is used as friction (cost) surface to compute the cost distance from any grid cell of the raster to the river. A characteristic value (default: the mean) of the cost distance distribution in a region surrounding the river (default: a buffer region of 2 km) is then calculated, and used to threshold the cost-distance surface. The resulting area is then "polygonized" to obtain the valley boundary as a simple feature geometry.

Usage

```
delineate_valley(dem, river)
```

Arguments

dem	SpatRaster object with the digital elevation model of the region
river	An object of class sf::sf or sf::sfc representing the river

Value

River valley as a simple feature geometry of class sfc_MULTIPOLYGON

Examples

```
bucharest_osm <- get_osm_example_data()
bucharest_dem <- get_dem_example_data()
delineate_valley(bucharest_dem, bucharest_osm$river_centerline)
```

---

delineation *The delineation class*

Description

An S3 class representing the result of a delineation as returned by delineate().

Value

An object of class delineation containing zero or more of the spatial layers $valley, $corridor, $segments, and $riverspace (each an sf::sfc_POLYGON or sf::sfc_MULTIPOLYGON object), plus the base OSM and optionally DEM layers and an $aoi list with the delineation parameters produced by define_aoi(). See delineate() for details.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
class(bd)
```

flatten_network *Flatten a network by adding points at apparent intersections*

Description

All crossing edges are identified, and the points of intersections are injected within the edge geometries. Note that the injected points are not converted to network nodes (this can be achieved via sfnetworks' `sfnetworks::to_spatial_subdivision()`, which is part of the tasks that are included in `clean_network()`.

Usage

```
flatten_network(network)
```

Arguments

network	A network object of class `sfnetworks::sfnetwork`

Details

The functionality is similar to sfnetworks' `sfnetworks::st_network_blend()`, but in that case an external point is only injected to the closest edge.

Value

An `sfnetworks::sfnetwork` object with additional points at intersections

Examples

```
bucharest_osm <- get_osm_example_data()
edges <- dplyr::bind_rows(bucharest_osm$streets,
                          bucharest_osm$railways)
network <- sfnetworks::as_sfnetwork(edges, directed = FALSE)
flatten_network(network)
```

geom_delineation *ggplot2 layer for a delineation object*

Description

Creates a list of `ggplot2::geom_sf()` layers representing the delineation results of a delineation object. The list can be added to a `ggplot2::ggplot()` object with +, and further layers or themes can be added on top. Base layers (`streets`, `railways`, `river_centerline`, `river_surface`) are not included and can be added separately with `ggplot2::geom_sf()`.

Usage

```
geom_delineation(x, extent = "corridor", legend = TRUE)
```

Arguments

x	An object of class delineation. This is typically the output of the delineate() function.
extent	The delineation layer whose bounding box sets the plot extent. One of "corridor", "valley", "riverspace", or NULL (no restriction, ggplot2 fits all layers). Defaults to "corridor".
legend	Whether the plot should display a legend. Default is TRUE.

Details

The following layers are included (where present in x), in the following order:

- corridor or riverspace (only when corridor is absent): drawn first to set the plot extent
- valley: light grey, transparent fill, no outlines
- segments: outlined polygons
- corridor: outlined polygon

Value

A list of ggplot2::geom_sf() and ggplot2::coord_sf() elements to be added to a ggplot2::ggplot() object.

See Also

plot.delineation() for a base R alternative.

Examples

```
library(ggplot2)
bd <- delineate_city_river("Bucharest", "Dâmbovița")
ggplot() + geom_delineation(bd) + theme_void()
ggplot() + geom_delineation(bd, extent = "valley") + theme_void()
```

get_dem *Access digital elevation model (DEM) for a given region*

Description

Access digital elevation model (DEM) for a given region

Usage

```
get_dem(
  aoi,
  osm,
  dem_source = "STAC",
  stac_endpoint = NULL,
  stac_collection = NULL,
  force_download = FALSE
)
```

Arguments

aoi	A list of delineation parameters, including `$dem_buffer` used to expand the area of interest covered by the network and `$crs` for the CRS which to transform the DEM to
osm	A list with OpenStreetMap data sets for the a location, as objects of class `sf::sfc`
dem_source	Source of the DEM: • If "STAC" (default), DEM tiles are searched on a SpatioTemporal Asset Catalog (STAC) end point, then accessed and mosaicked to the area of interest
stac_endpoint	URL of the STAC API endpoint (only used if `dem_source` is `"STAC"`). For more info, see `get_stac_asset_urls()`
stac_collection	Identifier of the STAC collection to be queried (only used if `dem_source` is `"STAC"`). For more info, see `get_stac_asset_urls()`
force_download	Download data even if cached data is available

Value

DEM as a terra `SpatRaster` object

Examples

```
# Define delineation parameters and get OSM data within area of interest
aoi <- define_aoi("Bucharest", "Dâmbovița")
osm <- get_osm(aoi)

# Get DEM with default values
```

```
dem <- get_dem(aoi, osm)

# Get DEM from custom STAC endpoint
get_dem(aoi, osm,
        stac_endpoint = "some endpoint",
        stac_collection = "some collection")

# Specify CRS
get_dem(bb, crs = crs)
```

`get_dem_example_data` *Get example DEM data*

Description

This function retrieves example Digital Elevation Model (DEM) data from the Zenodo data repository, and it can be used in examples and tests. The code used to generate the example dataset is available at https://github.com/CityRiverSpaces/CRiSpExampleData. Note that the example dataset is cached locally, so that subsequent calls to the function can load the example data from disk without having to re-download the data.

Usage

```
get_dem_example_data(force_download = FALSE)
```

Arguments

`force_download`	Download data even if cached data is available

Value

An object of class `terra::SpatRaster` containing the DEM data.

Examples

```
get_dem_example_data(force_download = TRUE)
```

get_osm *Retrieve OpenStreetMap data for a given location*

Description

Retrieve OpenStreetMap data for a given location, including the city boundary, the river centreline and surface, the streets, the railways, and the buildings

Usage

```
get_osm(
  aoi,
  city_boundary = TRUE,
  network = TRUE,
  buildings = TRUE,
  force_download = FALSE
)
```

Arguments

aoi	A list of delineation parameters
city_boundary	A logical indicating if the city boundary should be retrieved. Default is TRUE.
network	A logical indicating if the spatial network should be retrieved. Default is TRUE.
buildings	A logical indicating if buildings should be retrieved. Default is TRUE.
force_download	Download data even if cached data is available

Value

A list with the retrieved OpenStreetMap data sets for the given location, as objects of class sf::sfc

Examples

```
# Set parameters
city <- "Bucharest"
river <- "Dâmbovița"

# Define AOI parameters
aoi <- define_aoi(city, river)

# Get OSM data with defaults
get_osm(aoi)

# Get OSM data without city boundary
get_osm(aoi, city_boundary = FALSE)

# Use custom network buffer to get streets and railways
aoi2 <- aoi
```

```
aoi2$network_buffer = 3500
get_osm(aoi2)

# Use custom buffer to get buildings
aoi3 <- aoi
aoi3$buildings_buffer = 150
get_osm(aoi3)

# Use custom CRS
aoi4 <- aoi
aoi4$crs <- "EPSG:31600"
get_osm(aoi4)

# Avoid getting OSM data from cache
get_osm(city_name = city, river_name = river, force_download = TRUE)
```

`get_osm_bb` *Get the bounding box of a city*

Description

Get the bounding box of a city

Usage

```
get_osm_bb(city_name)
```

Arguments

`city_name`	A character vector of length one

Value

A bbox object with the bounding box of the city

Examples

```
get_osm_bb(city_name = "Bucharest")
```

get_osm_buildings *Get OpenStreetMap buildings*

Description

Get buildings from OpenStreetMap within a given buffer around a river.

Usage

```
get_osm_buildings(aoi, crs = NULL, force_download = FALSE)
```

Arguments

aoi	Area of interest as sf object or bbox
crs	Coordinate reference system as EPSG code
force_download	Download data even if cached data is available

Value

An object of class sf::sfc_POLYGON

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_buildings(aoi = bb, crs = crs)
```

get_osm_city_boundary *Get the city boundary from OpenStreetMap*

Description

This function retrieves the city boundary from OpenStreetMap based on a bounding box with the OSM tags "place:city" and "boundary:administrative". The result is filtered by the city name.

Usage

```
get_osm_city_boundary(
  bb,
  city_name,
  crs = NULL,
  multiple = FALSE,
  force_download = FALSE
)
```

Arguments

bb	Bounding box of class bbox
city_name	A case-sensitive character vector of length 1 with the name of the city
crs	Coordinate reference system as EPSG code
multiple	A logical indicating if multiple city boundaries should be returned. By default, only the first one is returned.
force_download	Download data even if cached data is available

Value

An object of class sf::sfc_POLYGON or sf::sfc_MULTIPOLYGON with the city boundary

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_city_boundary(bb = bb, city_name = "Bucharest", crs = crs)
```

---

get_osm_example_data *Get example OSM data*

Description

This function retrieves example OpenStreetMap (OSM) data from the Zenodo data repository, and it can be used in examples and tests. The code used to generate the example dataset is available at https://github.com/CityRiverSpaces/CRiSpExampleData. Note that the example dataset is cached locally, so that subsequent calls to the function can load the example data from disk without having to re-download the data.

Usage

```
get_osm_example_data(force_download = FALSE)
```

Arguments

force_download	Download data even if cached data is available

Value

A list of sf objects containing the OSM data as sf::sfc objects.

Examples

```
get_osm_example_data(force_download = TRUE)
```

get_osm_railways *Get OpenStreetMap railways*

Description

Get OpenStreetMap railways

Usage

```
get_osm_railways(
  aoi,
  crs = NULL,
  railway_values = "rail",
  force_download = FALSE
)
```

Arguments

aoi	Area of interest as sf object or bbox
crs	A numeric vector of length one with the EPSG code of the CRS
railway_values	A case-insensitive character vector with the railway values to retrieve.
force_download	Download data even if cached data is available

Value

An object of class sf::sfc_LINESTRING

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_railways(aoi = bb, crs = crs)
```

get_osm_river_centerline *Get the river centreline from OpenStreetMap*

Description

Get the river centreline from OpenStreetMap

Usage

```
get_osm_river_centerline(
  bb,
  river_name,
  crs = NULL,
  buffer_distance = NULL,
  force_download = FALSE
)
```

Arguments

bb	Bounding box of class bbox
river_name	The name of the river as character vector of length 1, case-sensitive.
crs	Coordinate reference system as EPSG code
buffer_distance	Optional buffer distance in metres to expand the bounding box before cropping the river centreline. Useful when downstream processing (e.g. network or DEM analysis) extends beyond the original bb. Defaults to NULL (no expansion).
force_download	Download data even if cached data is available

Value

The river centreline as object of class sf::sfc_LINESTRING or sf::sfc_MULTILINESTRING.

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_river_centerline(bb = bb, river_name = "Dâmbovița", crs = crs,
              force_download = FALSE)
```

---

get_osm_river_surface *Get the river surface from OpenStreetMap*

Description

Get the river surface from OpenStreetMap

Usage

```
get_osm_river_surface(bb, river_centerline, crs = NULL, force_download = FALSE)
```

Arguments

bb	Bounding box of class bbox
river_centerline	The river centerline as an object of class sf::sfc_LINESTRING or sf::sfc_MULTILINESTRING
crs	Coordinate reference system as EPSG code
force_download	Download data even if cached data is available

Value

The river surface as object of class sf::sfc_POLYGON or sf::sfc_MULTIPOLYGON.

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
river <- get_osm_river_centerline(bb, "Dâmbovița")
get_osm_river_surface(bb = bb, river_centerline = river, crs = crs,
              force_download = FALSE)
```

---

get_osm_streets *Get OpenStreetMap streets*

Description

Get OpenStreetMap streets

Usage

```
get_osm_streets(aoi, crs = NULL, highway_values = NULL, force_download = FALSE)
```

Arguments

aoi	Area of interest as sf object or bbox. Required, no default.
crs	A numeric vector of length one with the EPSG code of the CRS
highway_values	A character vector with the highway values to retrieve. If left NULL, the function retrieves the following values: "motorway", "trunk", "primary", "secondary", "tertiary"
force_download	Download data even if cached data is available

Value

An object of class sf::sfc_LINESTRING

Examples

```
# Set parameters
bb <- get_osm_bb("Bucharest")
crs <- 31600  # National projected CRS

# Get streets with default values
get_osm_streets(aoi = bb, crs = crs)

# Specify street categories to be retrieved
get_osm_streets(aoi = bb, crs = crs, highway_values = "primary")

# Ensure that data is not retrieved from cache
get_osm_streets(aoi = bb, crs = crs, force_download = FALSE)
```

---

get_river_aoi *Get an area of interest (AoI) around a river, cropping to the bounding box of a city*

Description

Get an area of interest (AoI) around a river, cropping to the bounding box of a city

Usage

```
get_river_aoi(river, city_bbox, buffer_distance)
```

Arguments

river	A sf::sf or sf::sfc object with the river centreline and (optionally) the river surface geometry
city_bbox	Bounding box of class bbox around the city
buffer_distance	A positive number representing the buffer size around the river in meters. The upper limit is unrestricted.

Value

An sf::sfc_POLYGON object in lat/lon coordinates

Examples

```
bb <- get_osm_bb("Bucharest")
river_centerline <- get_osm_river_centerline(bb, "Dâmbovița")
river_surface <- get_osm_river_surface(bb, "Dâmbovița")
river <- list(centerline = river_centerline, surface = river_surface)
get_river_aoi(river = river, city_bbox = bb, buffer_distance = 100)
```

get_stac_asset_urls *Retrieve the URLs of all the assets intersecting a bbox from a STAC API*

Description

Retrieve the URLs of all the assets intersecting a bbox from a STAC API

Usage

```
get_stac_asset_urls(bb, endpoint = NULL, collection = NULL)
```

Arguments

bb	A bounding box, provided either as a matrix (rows for "x", "y", columns for "min", "max") or as a vector ("xmin", "ymin", "xmax", "ymax"), in lat/lon coordinates (WGS84 coordinate referece system) of class bbox
endpoint	URL of the STAC API endpoint. To be provided together with stac_collection, or leave blank to use defaults (see default_stac_dem)
collection	Identifier of the STAC collection to be queried. To be provided together with stac_endpoint, or leave blank to use defaults (see default_stac_dem)

Value

A list of URLs for the assets in the collection overlapping with the specified bounding box

Examples

```
bb <- get_osm_bb("Bucharest")
get_stac_asset_urls(bb)

# Use non-default STAC API
get_stac_asset_urls(bb,
                    endpoint = "some endpoint",
                    collection = "some collection")
```

get_utm_zone *Get the UTM zone of a spatial object*

Description

Get the UTM zone of a spatial object

Usage

```
get_utm_zone(x)
```

Arguments

x	Object in any class accepted by as_bbox()

Value

The EPSG code of the UTM zone

Examples

```
# Get EPSG code for UTM zone of Bucharest
bb <- c(xmin = 25.97, ymin = 44.33, xmax = 26.23, ymax = 44.54)
get_utm_zone(bb)
```

---

load_dem *Retrieve DEM data from a list of STAC assets*

Description

Load DEM data from a list of tiles, crop and merge using a given bounding box to create a raster DEM for the specified region. Results are cached, so that new queries with the same input parameters will be loaded from disk.

Usage

```
load_dem(bb, tile_urls, force_download = FALSE)
```

Arguments

bb	A bounding box, provided either as a matrix (rows for "x", "y", columns for "min", "max") or as a vector ("xmin", "ymin", "xmax", "ymax") of class bbox.
tile_urls	A list of tiles where to read the DEM data from
force_download	Download data even if cached data is available

Value

A DEM of class terra::SpatRaster, retrieved and retiled to the given bounding box

Examples

```
bb <- get_osm_bb("Bucharest")
tile_urls <- get_stac_asset_urls(bb)
load_dem(bb = bb, tile_urls = tile_urls, force_download = TRUE)
```

osmdata_as_sf *Retrieve OpenStreetMap data as sf object*

Description

Query the Overpass API for a key:value pair within a given bounding box (provided as lat/lon coordiates). Results are cached, so that new queries with the same input parameters will be loaded from disk.

Usage

```
osmdata_as_sf(key, value, aoi, force_download = FALSE)
```

Arguments

key	A case-insensitive character vector of length 1 with the key to filter the data
value	A case-insensitive character vector with the value(s) to filter the data
aoi	An area of interest, provided either as as sf object or "bbox" or as a vector ("xmin", "ymin", "xmax", "ymax")
force_download	Download data even if cached data is available

Value

An osmdata::osmdata object with the retrieved OpenStreetMap data

Examples

```
bb <- get_osm_bb("Bucharest")
osmdata_as_sf(key = "highway",
              value = "motorway",
              aoi = bb,
              force_download = FALSE)
```

plot.delineation *Plot a delineation object*

Description

This S3 method provides a way to quickly visualise how the layers of a delineation object fit together using base R graphics. A delineation object typically includes the base layers streets, railways, river_centerline and river_surface, and the delineations of the valley, corridor, segments, and riverspace. Depending on the delineation object, some of the delineation layers may not be present and thus will not be plotted.

Usage

```
## S3 method for class 'delineation'
plot(x, ..., legend = TRUE)
```

Arguments

x	An object of class delineation, which is typically the output of the `delineate()` function.
...	Not used; included for compatibility with the generic.
legend	logical. If TRUE (default), a legend is added to the plot.

Value

NULL, invisibly. This function is called for its side effect of producing a plot.

See Also

`geom_delineation()` for a ggplot2-based alternative.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
plot(bd)
```

---

print.delineation *Print a delineation object*

Description

Prints a compact summary of a delineation object, showing which layers are present and their feature counts.

Usage

```
## S3 method for class 'delineation'
print(x, ...)
```

Arguments

x	An object of class delineation.
...	Not used; included for compatibility with the generic.

Value

x, invisibly.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
print(bd)
```

`print.summary.delineation` *Print a summary.delineation object*

Description

Print a summary.delineation object

Usage

```
## S3 method for class 'summary.delineation'
print(x, ...)
```

Arguments

`x`	An object of class `summary.delineation`, as returned by `summary.delineation()`.
`...`	Not used; included for compatibility with the generic.

Value

`x`, invisibly.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
s <- summary(bd)
print(s)
```

`reproject` *Reproject a raster or vector dataset to the specified coordinate reference system (CRS)*

Description

Reproject a raster or vector dataset to the specified coordinate reference system (CRS)

Usage

```
reproject(x, crs, ...)
```

Arguments

x	Raster (SpatRaster) or vector (sf) object
crs	CRS to be projected to, provided as numeric, integer or character vector of length one or sf::crs. If numeric, the value should be a positive number with unrestricted upper bound representing a valid EPSG code.
...	Optional arguments for raster or vector reproject functions

Value

sf::sf, sf::sfc, or terra::SpatRaster object reprojected to specified CRS

Examples

```
# Reproject a raster to EPSG:4326
r <- terra::rast(matrix(1:12, nrow = 3, ncol = 4), crs = "EPSG:32633")
reproject(r, 4326)
```

---

summary.delineation *Summarise a delineation object*

Description

Computes summary statistics for a delineation object and returns them as a structured list of class summary.delineation. Delineation layers are reported with their area (in km²). For segments, the number of features and mean area are also given. Base layers are reported with feature counts; river_centerline as total length (in km) and river_surface as area (in km²).

Usage

```
## S3 method for class 'delineation'
summary(object, ...)
```

Arguments

object	An object of class delineation.
...	Not used; included for compatibility with the generic.

Value

An object of class summary.delineation, which is a named list with elements city_name, river_name, crs, parameters, delineation_layers, and base_layers. parameters contains network_buffer, dem_buffer, and buildings_buffer (in metres), or NULL if no aoi was stored. Each layer entry is itself a named list of stats, or NULL if the layer is absent.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
s <- summary(bd)
s$delineation_layers$corridor$area_km2
```

Index

∗ **datasets**
    bucharest_dambovita, 5

as.Date(), *7*
as_bbox, 3
as_bbox(), *30*
as_crs, 3
as_network, 4

bucharest_dambovita, 5

cache_directory, 6
cap_corridor(), *10*, *13*
check_cache, 6
clean_network, 7
clean_network(), *5*, *17*
clear_cache, 7
corridor_edge(), *10*, *13*

Date, *7*
default_stac_dem, 8, *29*
define_aoi, 8
define_aoi(), *10*, *16*
delineate, 10
delineate(), *16*, *18*, *32*
delineate_city_river, 11
delineate_corridor, 12
delineate_riverspace, 14
delineate_segments, 15
delineate_segments(), *10*
delineate_valley, 15
delineate_valley(), *10*
delineation, *11*, 16, *18*, *32*

flatten_network, 17

geom_delineation, 17
geom_delineation(), *32*
get_dem, 19
get_dem_example_data, 20
get_osm, 21
get_osm_bb, 22
get_osm_buildings, 23
get_osm_city_boundary, 23
get_osm_example_data, 24
get_osm_railways, 25
get_osm_river_centerline, 25
get_osm_river_surface, 26
get_osm_streets, 27
get_river_aoi, 28
get_stac_asset_urls, 29
get_stac_asset_urls(), *19*
get_utm_zone, 29
ggplot2::coord_sf(), *18*
ggplot2::geom_sf(), *17*, *18*
ggplot2::ggplot(), *17*, *18*

load_dem, 30

osmdata::osmdata, *31*
osmdata_as_sf, 31

plot.delineation, 31
plot.delineation(), *18*
print.delineation, 32
print.summary.delineation, 33

rcoins::stroke(), *10*, *15*
reproject, 33

sf::bbox, *9*
sf::crs, *4*, *9*, *34*
sf::sf, *4*, *10*, *13*, *15*, *16*, *34*
sf::sfc, *10*, *13*, *15*, *16*, *19*, *21*, *24*, *34*
sf::sfc_LINESTRING, *4*, *25–27*
sf::sfc_MULTILINESTRING, *26*, *27*
sf::sfc_MULTIPOLYGON, *11*, *16*, *24*, *27*
sf::sfc_POLYGON, *11–16*, *23*, *24*, *27*, *28*
sf::st_bbox(), *3*
sfnetworks::sfnetwork, *5*, *7*, *13*, *17*
sfnetworks::st_network_blend(), *17*

sfnetworks::to_spatial_subdivision(), *17*
simplify_network(), *7*
summary.delineation, 34
summary.delineation(), *33*

terra::SpatRaster, *20*, *30*, *34*
tools::R_user_dir(), *6*